


# 深圳中陇天包装科技有限公司

SHENZHEN ZOLO PACKAGING TECHNOLOGY CO.,LTD

## 材料材质报告

### Material Report

品名 Article Name	38#哑巴哑面OPEN VOID不转移防伪材料 38# matte blue OPEN VOID non residue label material	内部品名 The internal name	38#蓝色哑面OPEN VOID不转移防伪材料	防伪类型 Anti fake type	不转移 Non residue	字体大小 Font Size	中号 Middle
产品结构 PRODUCTION CONSTRUCTION							
面材 SURFACE MATERIAL	底纸 LINER						
材料名称 Article Name	PET		材料名称 Article Name	格拉辛离型纸 GLASSINE RELEASE PAPER			
厚度(mm) THICKNESS	0.038±0.002		厚度(mm) THICKNESS	0.07±0.003			
颜色 COLOR	蓝色 Blue		颜色 COLOR	白色 White			
基重(g/m2) BASIC WEIGHT	/		基重(g/m2) BASIC WEIGHT	80±5			
平滑度 SMOOTHNESS	GOOD		平滑度 SMOOTHNESS	GOOD			
印刷性 PRINT ABILITY	GOOD		离型力(g/in) Release force	原材料 (德莎胶带测试) 成品 (180° PEEL ADHESIVE)	3 ~ 8 2 ~ 4		
表面涂层处理(mm) Surface treatment	0.002±0.001		VOID印刷涂层厚度(mm) VOID layer print thickness	0.003±0.001			

#### 粘 胶

#### PRESSURE SENSITIVE ADHESIVE

胶系 ADHESIVE	压克力/snjs01 ACRYLIC	保持力 (hr/kg×inch) HOLDING POWER	≥24H ↑
上胶厚度 (mm) THICKNESS	0.045±0.003	剥离力(Kgf/inch) 180° PEEL ADHESIVE	≥0.2 ↑
上胶量 (g/m2) DRY COATING WEIGHT	130±5	适用温度(°C) TEMPERATURE RANGE	-15 ~ 70
初粘力(NO/BALL) INITIAL TACK	6 ~ 9	耐候性 WEATHER RESISTANCE	GOOD
保存期限 SHELF LIFE		1 year, under room(normal) temperature	

#### 备注:

以上各项技术资料是本公司采用公认可靠之检验方法, 经多次检验所得平均数据. 但为确保正确选择与使用本公司之产品, 请您基于使用之对象, 先行对使用目的与条件作详尽了解与试用, 或通知本公司, 以便为您更进一步说明与服务.

#### REMARK:

THE TECHNICAL DATA ARE BASED ON THE RELIABLE EXPERIMENT CARRIED BY THE COMPANY, WHICH HOWEVER ARE NOT TO GAURANTEE THOSE PROPERTIES AND CHARACTERISTICS COMPLETELY AS SPECIFIED THEREIN, KINDLY STUDY YOUR PURPOSE AND CONDITION TO USE THIS PRODUCT PREVIOUSLY IN DETAIL UPON YOUR OWN RESPONSIBILITY.

拟定人 Made by	Chris	拟定日期 Date of draft	201905	版本号 Version number	V3
----------------	-------	-----------------------	--------	-----------------------	----